

Appl. No. : 10/603,426
Filed : June 24, 2003

AMENDMENTS TO THE SPECIFICATION

Please replace paragraph number [0143] of the filed specification (number [0168] of the publication) with the following rewritten paragraph:

Subsequently the patterned resist is stripped. The oxide layer on top of the exposed first polysilicon layer 3 is removed. Then the first polysilicon layer 3 is etched self-aligned using the patterned first 4 and second 5 hard mask region to protect the underlying first polysilicon layer 3. As the second hardmask 5 is also polycrystalline silicon the spacer formed in the 2nd polysilicon layer 9 to define the program lines 33a-f as discussed in the previous embodiments of this aspect is removed while etching the first poly layer 3. Simultaneously, the patterned second poly 9₅ is removed in the contact pad areas 41 while also defining the size of these areas. Then, the junctions 6 are implanted selfaligned to the patterned first polysilicon layer 3 in order to form the bitlines 6 as shown in figure 8c.

Please replace paragraph number [0146] of the filed specification (number [0171] of the publication) with the following rewritten paragraph:

The exposed gate dielectric 60₂ is also removed. This is the gate dielectric at the bottom of the cavity 61 created by removing the first patterned hard mask 4 and the underlying first polysilicon layer 3. A second gate dielectric is deposited which could be an oxide or again a combined ONO layer for the case of a quadruple-bit cell as discussed in the fourth and fifth embodiment of the present invention. A next, i.e. third, polysilicon layer is deposited on top of the substrate. This second gate electrode material or third polysilicon layer is patterned to form the wordline 80 of the dual-bit structure in a fully self-aligned manner in a direction perpendicular to the bitlines 6 as discussed in previous embodiments of this aspect and as shown in figure 8f.

BEST AVAILABLE COPY

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.